



### Main

Range of product	Conext RL
Device short name	RL 4000 E
Product or component type	Grid-tie solar inverter
Network number of phases	Single phase
Nominal output power	4 kVA

### Complementary

Photovoltaic power	4.2 kW input power for maximal output power 3.2 kW input power per MPPT
Output voltage	184...276 V AC 230 V AC (nominal)
Number of MPPT	2
Maximum output current	18.2 A AC
Frequency	50/60 Hz +/- 5 Hz (output)
Cos phi	0.8 leading to lagging
Harmonic distortion	< 3 %
Input voltage	100 V DC at start 180...500 V DC MPPT 90...550 V DC operating <= 550 V DC open circuit
Input current per MPPT	<= 12 A
Efficiency	97.5 % peak 97 % European
Power consumption in W	< 1 W night time
Topology	Transformerless
Function available	Standard integrated DC disconnect (optional) Embedded data logger for 365 days
Relay type	Multifunction control relay
Display type	LCD
Messages display capacity	2 lines of 16 characters
Communication interface	Ethernet (optional) Modbus (RS485)
Type of connector	- (IP67 - output) Multicontact MC4 - input)
Type of cooling	Natural convection
Height	42 cm
Width	48 cm
Depth	16 cm
Product weight	21 kg
Acoustic level	< 40 dBA
Enclosure material	Aluminium

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

IP degree of protection	IP65 (balance) IP65 (electronic)
Ambient air temperature for operation	-20...65 °C
Electromagnetic compatibility	Immunity for industrial environments conforming to EN 61000-6-2 Emission standard for residential, commercial and light-industrial environments conforming to EN 61000-6-3
Standards	VDE 0126 AS 3100 VDE-AR-N 4105 RD 1699 CEI 0-21 IEC 62116 IEC 61727 AS 4777 EN 50438 G83/1 engineering recommendation UTE C 15-712-1 AS 5033
Product certifications	CE marked for low voltage directive 2006/95/EC conforming to 62109-1/62109-2 CE marked for EMC directive 2004/108/EC
Operating altitude	< 2000 m
Relative humidity	4...100 % (condensing)
Environmental characteristic	Stationary use at non-weatherprotected locations, category 4K4H conforming to IEC 60721-3-4 REACH